

Tarex Red 10W-40 Semi-Synthetic

Product description:

Tarex Red 10W-40 is fuel economy, universal motor oil developed according the most recent technology, based on specially selected synthetic base-stocks and a well balanced choice of advanced additives. It provides outstanding thermal and oxidation stability, extended oil drain intervals, referring to the recommendation of the OEMs manufacturer.

Specifications and approvals: Tarex Red 10W-40 meets or exceeds the following industry specifications:

ACEA 2002 A3-02 B4-02 B3-98 Part 2

ACEA 2004 A3/B4-04 A3/B3-04

API SL/CF

BMW Spezialoel

MB 228.1/229.1

SAE 10W-40

VW/AUDI 502 / 505

Parameter	Unit of measure	Data	Test method
Color		3,5	
Density (at 15°C)	g/ml	0.871	DIN 51757
Viscosity (at -25°C)	mPa.s	6900	DIN 51377
Viscosity (at 40°C)	mm ² /s	99	DIN 51562
Viscosity (at 100°C)	mm ² /s	14.7	DIN 51562
VI		144	DIN ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592
Pour	°C	-35	DIN ISO 3016
TBN	mg KOH/g	9	DIN ISO 3771
Sulphated ash	%	0.89	DIN 51 575

These specifications show average values and may change from batch to batch within the tolerances of the standards.