

Tarmax Super 15W40 and 20w50 Motor Oil

Product description;

Conditions designed for secondary operations, as well refined base oils and advanced additive technology that combines high-quality motor oil. Tarmax Super 15w40 and 20W50 has standart oil change interval.

Spesifications and approvals:Tarmax Super 15W40 and 20W50 meets or exceeds the following industry specifications;

API CF-4

ACEA E2-B3

MB 228.1

MAN 270/271

Volvo VDS

Features and benefits:

*Not effected by high temperature changes.

*Improved engine cleaning feature keeps the engine clean.

*Contains molecules that prevents corrosion.

*Superior protection four season.

15w40

Viscosity (at 40°C)	mm ² /s	100-110	ASTM D445
Viscosity (at 100°C)	mm ² /s	14-15,6	ASTM D445
VI		130	ASTM D2270
Flash point (COC)	°C	230	ASTM D92
Pour	°C	-27	ASTM D97
TBN	mg KOH/g		DIN ISO 3771
Density	gr/ml	0,885	ASTM D1298

20w50

Viscosity (at 40°C)	mm ² /s	160-175	ASTM D445
Viscosity (at 100°C)	mm ² /s	19-20	ASTM D445
VI		122	ASTM D2270
Flash point (COC)	°C	230	ASTM D92
Pour	°C	-24	ASTM D97
TBN	mg KOH/g		DIN ISO 3771
Density	gr/ml	0,89	ASTM D1298