

Tarmax Turbo 15W40 SHPD Motor Oil

Product description:

New formulation specifically developed for high performance diesel engines. Tarmax Turbo 15W40 Multigrade prolongs engine life and extends oil drain intervals. It is suitable for both turbo and non-turbo charged engines. Well recognised by European, Japanese and American engine manufacturers, Tarmax turbo mended for heavy equipment used in construction work leading farming engine manufacturers such as John Deer, Case-New Holland and Massey Ferguson.

Specifications and approvals; Tarmax Turbo 15W40 meets or exceeds the following industry specifications:

API CG 4,CH 4

ACEA E3-B3

MB 228 3

MAN M 3275

Volvo VDS -2

Features and benefits:

*Not effected by high temperature changes.

*Improved engine cleaning feature keeps the engine clean.

*Contains molecules that prevents corrosion.

*Superior protection four season.

Viscosity (at 40°C)	mm ² /s	100-110	ASTM D445
Viscosity (at 100°C)	mm ² /s	14-15,6	ASTM D445
VI		133	ASTM D2270
Flash point (COC)	°C	230	ASTM D92
Pour	°C	-27	ASTM D97
TBN	mg KOH/g		DIN ISO 3771
Density	gr/ml	0,885	ASTM D1298