



Our company has been in GebzeKocaeli since 1980
15.000 square meters of installed on the premises of
the Automotive and Industrial field of special oils and
antifreeze production continues.

Tarimsan Tarim Sanayi ve Tic. A.S.

Istasyon Mah. Beyazit Cad. 24, Gebze41700/ Kocaeli

e-mail: info@tarmond.com

Phone: +90 262 655 98 50

TARMAX TURBO BLU 5W-40

ULTRA HIGH PERFORMANCE SYNTHETIC DIESEL OIL

Product Description:

TARMAX TURBO BLU 5W-40 is a Synthetic Ultra High Performance Diesel (UHPD) engine oil for use in heavy-duty turbo-diesel engines of trucks, buses and industrial engines. The oil is engineered with synthetic blend technology to meet the long-life requirements of major engine manufacturers and gives protection over a long time period. TARMAX TURBO BLU 5W-40 provides lubrication to modern, high performance, low emissions engines used in severe applications. This engine oil is designed using the high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control.

Applications:

Suitable for heavy-duty fleets working under severe conditions. Suitable for extended oil drain intervals in heavy duty trucks, buses and off-road machinery where API CI-4 performance level is recommended.

Benefits:

- Outstanding protection against oil thickening, high temperature deposits, sludge build-up and, oil degradation
- Excellent anti-wear, anti-scuff properties and bore polishing and corrosion protection.
- Stay-in-grade shear stability with low volatility.
- Good low temperature properties

Meets Performance:

ACEA E7-12, E5-02, E4-98; API CI-4, CH-4; MAN M 3277; MB 228.5; Volvo VDS-3; Renault

RLD/RLD-2

Technical Data:

TARMAX TURBO BLU 5W-40	Test method	
API		CI-4
SAE Grade		5W-40
Density at 15°C gr/cm ³	ASTM D 1298	0,87
Viscosity at 40°C c St	ASTM D 445	90-95
Viscosity at 100°C c St	ASTM D 445	13,0-14,2
Viscosity Index	ASTM D 2270	156 min.
Flash point °C	ASTM D 92	220
Pour point °C	ASTM D 97	-30