

Our company has been in GebzeKocaeli since 1980 15.000 square meters of installed on the premises of the Automotive and Industrial field of special oils and antifreeze production continues.

Tarimsan Tarim Sanayi ve Tic. A.S. Istasyon Mah. Beyazit Cad. 24, Gebze41700/ Kocaeli e-mail: info@tarmond.com Phone: +90 262 655 98 50

TARMOND AGRO F426

TRANSMISSION AND HYDRAULIC SYSTEM OILS

Product Description:

AGRO F 426 is an extra high performance, multipurpose **U**niversal **T**ractor **T**ransmission **O**il (UTTO), engineered to meet or exceed transmission and hydraulic fluid requirements. This product is formulated for the service top-up and refill of transmissions, final drives, and hydraulic systems of farm and industrial tractors and other off-highway equipments and especially those with oil-immersed brake systems. This product is designed with special frictional characteristics to prevent squawk and chatter noise in wet brake systems to deliver consistent braking performance.

Benefits:

- Improved low temperature stability
- Helps reduce wet brake chatter noise
- Suitable for most agricultural machinery requirements
- Keeps systems clean and operating smoothly
- All-season performance with consistent hydraulic operations.

Meets Performance: API GL-4; Allison C-4; Caterpillar T0-2; Massey Ferguson M-1145; Ford New Holland ESN-MC2-134D; Case MS 1204; John Deere J20C

Technical Data:

| | , mtu , mtu , mtu , mtu , mtu , mtu | |
|-------------------------|-------------------------------------|--------|
| TARMOND AGRO F 426 | Test method | |
| API | | GL-4 |
| SAE Grade | | 10W-30 |
| Density at 15°C gr/cm³ | ASTM D 1298 | 0,88 |
| Viscosity at 40°C c St | ASTM D 445 | 59 |
| Viscosity at 100°C c St | ASTM D 445 | 9,7 |
| Viscosity Index | ASTM D 2270 | 145 |
| Flash point °C | ASTM D 92 | 220 |
| Pour point °C | ASTM D 97 | -27 |

Above values are the typical values of the products and may vary with each batch.