



TAREX AGRO F426 UTTO

TRANSMISSION AND HYDRAULIC SYSTEM OIL for TRACTORS

Product Description:

TAREX AGRO F426 UTTO Transmission and Hydraulic System Oil is an extra high performance, multipurpose Universal Tractor Transmission Oil (UTTO), engineered to meet or exceed transmission and hydraulic fluid requirements. It is formulated for the service top-up and refill of transmissions, final drives, hydraulic systems of farm, industrial tractors, other off-highway equipments, and especially those with oil-immersed brake systems. TAREX AGRO F426 UTTO is designed with special frictional characteristics to prevent squawk and chatter in wet brake systems and to deliver consistent braking performance.

Applications:

TAREX AGRO F426 UTTO Transmission and Hydraulic System Oil is recommended for all tractor OEMs especially with wet brake systems.

Benefits:

- ❖ Improved low temperature stability
- ❖ Helps reduce wet brake noise
- ❖ Suitable for most agricultural machinery requirements
- ❖ Keeps systems clean and operating smoothly
- ❖ All-season performance with consistent hydraulic operation

Meets the performances:

JD J20C; D Volvo VCE 1273.03; WB 101; CASE; MAT 3505/3525/3526; Vickers I286S, M2950S, M2952S; FORD ESN M2C86B-C; Allison C4; MF M1145; CAT TO-2; White Q1826; Denison HF0/HF1/HF2; ZF TE-ML 03E/F, 05F, 06E/F/K, ZF TE-ML 17E/21F

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test method	
SAE Grade		F426
Density at 15°C gr/cm³	ASTM D 1298	0.86-0.87
Viscosity at 40°C cSt	ASTM D 445	55-65
Viscosity at 100°C cSt	ASTM D 445	9.3-9.9
CCS Viscosity at -30°C mPa.s	ASTM D 5293	Max. 7000
Viscosity Index	ASTM D 2270	142
Flash point °C	ASTM D 92	226
Pour point °C	ASTM D 97	-42

Above values are the typical values of the products and may vary with each batch