



TAREX ATF M/V

MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID

Product Description:

TAREX ATF M/V Multi-Vehicle Automatic Transmission Fluid is a premium formulation of synthetic base oils and highly sophisticated additive package that provides superior protection and performance in transmission. It provides extended service life, improved low and high temperature stability, severe service and any – wear protection. Specially formulated to meet the needs of a broad range of light and heavy duty automatic transmissions fitted with or without torque converter lock-up clutch. High performance, multipurpose automatic transmission fluid (ATF) provides outstanding oxidation resistance and anti-shudder durability protection.

Applications:

TAREX ATF M/V Multi-Vehicle Automatic Transmission Fluid is a premium lubricant for car and truck automatic transmissions. It can be used in all of the latest models from the major car manufacturers including Toyota, Nissan, Honda, Mitsubishi, Audi, Ford, and General Motors.

Benefits:

- ❖ Long fluid life and long transmission life
- ❖ Exceptional oxidation stability and resistance to chemical deterioration
- ❖ Excellent shear stability and viscosity stability (high viscosity index)
- ❖ Excellent flow properties at low start-up temperatures and high operating temperatures
- ❖ Excellent lubricating characteristics for quiet operation, smooth shifting
- ❖ Excellent wear protection
- ❖ Helps assure adequate lubrication without excessive thinning in severe high-temperature service or thickening at low starting temperatures
- ❖ Unique protection against rust and corrosion

Meets the Performances:

GM DEXRON II, IIIG, IIH; Allison C-4; FORD MERCON; Chrysler MS-9652/ATF-Plus/ATF+2/ATF+3/ATF+4; MAN 339A/339C, MB 236.5/236.6; JASO 1-A-LV-15, Toyota T III, T IV; ZF: TE-ML 11A/11B; Volvo 97341

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test method	
		ATF M/V
Density at 15°C gr/cm ³	ASTM D 1298	0.85-0.86
Viscosity at 40°C cSt	ASTM D 445	30-35
Viscosity at 100°C cSt	ASTM D 445	7.2-7.5
Viscosity Index	ASTM D 2270	Min. 140
Flash point °C	ASTM D 92	220
Pour point °C	ASTM D 97	-43

Above values are the typical values of the products and may vary with each batch.