



TAREX Blu 5W-30 SN

FULL SYNTHETIC MOTOR OIL – SN/CF

Product Description:

TAREX Blu 5W-30 SN Full Synthetic Motor Oil – SN/CF that is formulated with high quality full synthetic base oil formula. It has advanced formulation with most effective additives and blended using latest technology. It is a fully-synthetic engine oil specially designed with improved fuel efficiency performance. It offers superb cold start protection therefore, reduces engine wear and tears significantly. The special additives added to contribute to a significant reduction in engine noise. It provides outstanding oxidation stability, long-life properties and extended drain intervals. It is produced expertly to maintain the efficiency of Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Applications:

It is designed for petrol and diesel engines, including turbocharged and fuel injection. The new formulation continues to meet the recommendation of all major automotive builders (OEMs) throughout Europe, America, Japan and Asia. With the TAREX Blu 5W-30 SN Full Synthetic Motor Oil – SN/CF you get the best in all-year protection.

Benefits:

- ❖ Excellent high-temperature/high shear performance
- ❖ Excellent overall lubrication at cold ambient temperatures
- ❖ Good fuel economy
- ❖ Maintains high oil pressure
- ❖ Very efficient anti-deposit and anti-black sludge power which maintains a clean engine
- ❖ Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperature
- ❖ Neutralization of the acids
- ❖ Exceptional oil film stability through anti-wear protection in all loads
- ❖ Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness

Meets the performance:

API SN/CF; ACEA A5/B5; BMW LL01; Renault RN 0700/0710; MB 229.3; VW 502.00/505.00; Ford WSS M2C9346-A/M2C929-A

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test method	
API		SN/CF
SAE Grade		5W-30
Density at 15°C gr/cm ³	ASTM D 1298	0.85-0.86
Viscosity at 40°C cSt	ASTM D 445	69-74
Viscosity at 100°C cSt	ASTM D 445	11.5-12.2
CCS Viscosity at -30°C, mPa.s	ASTM D 5293	Max. 6600
Viscosity Index	ASTM D 2270	156
Flash point °C	ASTM D 92	225
Pour point °C	ASTM D 97	-42
Total Base Number mg KOH/g	ASTM D 2896	7.5-8
Sulphated Ash %	ASTM D 874	1.1

Above values are the typical values of the products and may vary with each batch.