



TAREX Blu 5W-40 SN

FULL SYNTHETIC MOTOR OIL – SN/CF

Product Description:

TAREX Blu 5W-40 SN FULL SYNTHETIC MOTOR OIL – SN/CF is a fully-synthetic engine oil specially designed for excellent performance under all conditions. It provides fast lubrication of the engine. It helps to extend engine life by protecting surface from wear and reduces engine deposits. The special additives added to contribute to a significant reduction in engine noise. It provides outstanding oxidation stability, long-life properties and extended drain intervals. It is produced expertly to maintain the efficiency of Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Applications:

It is designed for petrol and diesel engines, including turbocharged and fuel injection. The new formulation continues to meet the recommendation of all major automotive builders (OEMs) throughout Europe, America, Japan and Asia. With the TAREX Blu 5W-40 SN Full Synthetic Motor Oil – SN/CF you get the best in all-year protection.

Benefits:

- ❖ Excellent high-temperature/high shear performance
- ❖ Excellent overall lubrication
- ❖ Maintains high oil pressure
- ❖ Very efficient anti-deposit and anti-black sludge power which maintains a clean engine
- ❖ Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperature
- ❖ Exceptional oil film stability through anti-wear protection in all loads
- ❖ Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness

Meets the performance:

API SN/CF; ACEA A3/B3/B4; BMW LL01; Renault RN 0700; MB 229.3; VW 502.00/505.00; Porsche A40; PSA B71 2296; FIAT 9.55535-G2; AVTOVAZ

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test method	
API		SN/CF
SAE Grade		5W-40
Density at 15°C gr/cm³	ASTM D 1298	0.85-0.86
Viscosity at 40°C cSt	ASTM D 445	87-90
Viscosity at 100°C cSt	ASTM D 445	13.9-14.4
Viscosity Index	ASTM D 2270	160
CCS Viscosity at -30°C, mPa.s	ASTM D 5293	Max. 6600
Flash point °C	ASTM D 92	235
Pour point °C	ASTM D 97	-41
Total Base Number mg KOH/g	ASTM D 2896	7.6-8
Sulphated Ash,%	ASTM D 874	1.1

Above values are the typical values of the products and may vary with each batch.