



TAREX GEAR-X5 80W-90 GL-5

GEAR OIL

Product Description:

TAREX GEAR-X5 80W-90 GL-5 Gear Oil is a multigrade automotive gearbox lubricant which consist of high quality base oils and an advanced additive technology with high viscosity index. It was designed to provide optimum protection under extreme load conditions and it protects the system against wear and oxidation. It prevents corrosion and foam. When the system is subject to high pressure, it continues to protect gearbox system with the same performance thanks to the highly polar extreme pressure additives. It is specifically designed for transaxles, gearboxes and also limited slip differentials. It does not need an additional friction modifier for use in limited slip differentials as the co-efficient of friction is high enough for 'non chatter' performance.

Applications:

It is used in the transmission and differential systems of modern passenger cars, heavy duty industrial equipment and vehicles.

Benefits:

- ❖ Enhanced EP properties, reduced gear wear and extended life in transmissions, gearboxes, and final drives
- ❖ Excellent thermal stability and resistance to high temperature oxidation, minimal deposits for long gear and bearing life
- ❖ Outstanding anti-wear performance, preventing premature failure and provide longer equipment life
- ❖ Excellent corrosion protection, preventing corrosion for increased equipment protection
- ❖ Good resistance to foaming, maintains film strength for effective lubrication
- ❖ Compatible with typical automotive seals and gaskets, minimum leakage and reduced contamination

Meets the Performances:

API GL-5, LSMIL-L-2105D, MAN 342; ZF TE-ML 08/07A; MB 235.23

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test method	
API		GL-5
SAE Grade		80W-90
Density at 15°C gr/cm³	ASTM D 1298	0.89-0.90
Viscosity at 40°C cSt	ASTM D 445	145-150
Viscosity at 100°C cSt	ASTM D 445	15.0-15.5
Viscosity Index	ASTM D 2270	102
Flash point °C	ASTM D 92	225
Pour point °C	ASTM D 97	-24

Above values are the typical values of the products and may vary with each batch.