



## **TAREX AGRO 10W-40 CI-4**

### **ULTRA HIGH PERFORMANCE DIESEL TRACTOR OIL**

#### **Product Description:**

TAREX AGRO 10W40 CI-4 Ultra High Performance Diesel Tractor Oil is an engine oil for use in heavy-duty turbo-diesel engines of tractors as well as on and off-highway equipment. The oil is engineered with synthetic blend technology to meet the long-life requirements of major engine manufacturers and gives protection over a long time period. TAREX AGRO 10W40 CI-4 Ultra High Performance Diesel Tractor Oil provides lubrication to modern, high performance, low emissions engines used in severe applications. This engine oil is designed using the high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control.

#### **Applications:**

Designed for use in latest European, US and Japanese tractors and heavy duty on- and off-highway equipment, including the new breed highly turbocharged and emission control designed engines. It is a premium choice for all modern tractors and agricultural equipment.

#### **Benefits:**

- ❖ Outstanding protection against oil thickening, high temperature deposits, sludge build-up, and oil degradation
- ❖ Excellent anti-wear, anti-scuff properties and bore polishing and corrosion protection.
- ❖ Stay-in-grade shear stability with low volatility.
- ❖ Good low temperature properties

#### **Meets the Performances:**

ACEA E7/E5; API CI-4, CH-4; Massey Ferguson 1139/1144; Ford New Holland M2C-159B; John Deere J27

**Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.**

#### **Technical Data:**

TAREX	Test method	
API		CI-4
SAE Grade		10W-40
Density at 15°C gr/cm <sup>3</sup>	ASTM D 1298	0.86-0.87
Viscosity at 40°C cSt	ASTM D 445	95-100
Viscosity at 100°C cSt	ASTM D 445	14.4-14.9
CCS Viscosity at -35°C mPa.s	ASTM D 5293	Max. 7000
Viscosity Index	ASTM D 2270	155
Flash point °C	ASTM D 92	235
Pour point °C	ASTM D 97	-41
Total Base Number mg KOH/g	ASTM D 2896	10.0-10.7
Sulphated Ash, %	ASTM D 874	1.3

Above values are the typical values of the products and may vary with each batch.