



TAREX TURBO 10W-40

SEMI-SYNTHETIC MOTOR OIL - CI-4/SL

Product Description:

TAREX TURBO 10W40 Semi-Synthetic Motor Oil CI-4/SL is a semi-synthetic engine oil for use in heavy duty turbo diesel engines of trucks, buses and industrial engines. The oil is engineered with synthetic blend technology to meet the long life requirements of major engine manufacturers and gives protection over a long time period. TAREX TURBO 10W40 Semi-Synthetic Motor Oil CI-4/SL provides lubrication to modern, high performance, low emissions engines used in severe applications. This engine oil is designed using the highest quality base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control.

Applications:

Suitable for heavy duty fleets working under severe conditions. Suitable for extended oil drain intervals in heavy duty trucks, buses and off road machinery where API CI-4 performance level is recommended.

Benefits:

- ❖ Outstanding protection against oil thickening, high temperature deposits, sludge build up and, oil degradation
- ❖ Excellent anti-wear, anti-scuff properties with bore polishing and corrosion protection
- ❖ Stay-in grade shear stability with low volatility
- ❖ Good low temperature properties
- ❖ Helps to improve oil circulation
- ❖ Protects against bearing wear
- ❖ Helps to reduce oil consumption under heavy duty & high temperature operating conditions

Meets the Performances:

ACEA E7-12; E5-02, E4-98; API CI-4/CH-4/CG-4/SL; MAN M 3277; MB 228.3/228.5; Volvo VDS-3; Scania LDF-3; Renault RLD/RLD-2; DEUTZ DQC-III-18; CATERPILLAR ECF-1A/ECF-2/TO-2; CUMMINS CES 20076/20077/20078; MTU OIL CATEGORY 1/OIL CATEGORY 2; JASO DH-1

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test method	
API		CI-4/SL
SAE Grade		10W-40
Density at 15°C gr/cm ³	ASTM D 1298	0.86-0.87
Viscosity at 40°C cSt	ASTM D 445	95-100
Viscosity at 100°C cSt	ASTM D 445	14.4-14.9
CCS Viscosity at -25°C, mPa.s	ASTM D 5293	Max. 7000
Viscosity Index	ASTM D 2270	155
Flash point °C	ASTM D 92	230
Pour point °C	ASTM D 97	-41
Total Base Number mg KOH/g	ASTM D 2896	10-10.7
Sulphated Ash,%	ASTM D 874	1.3

Above values are the typical values of the products and may vary with each batch.