



TAREX TURBO 15W-40

DIESEL MOTOR OIL - CH-4/SL

Product Description:

TAREX TURBO 15W-40 CH-4 is a heavy duty multi-grade diesel engine oil designed for use high speed, four stroke diesel engines meeting the requirements of American, European and Japanese engine manufactures.

Applications:

It has been formulated for heavy duty service in engines specifically designed for on-highway conditions as well as being suitable for a wide range of heavy-duty off-highway applications.

Benefits:

- ❖ Helps control oil thickening and provides outstanding filterability
- ❖ Provide increased resistance to thermal breakdown
- ❖ Provides optimum protection and control of corrosion, piston deposits, oxidation, sludge build-up
- ❖ High level detergent-dispersant properties to keep engine clean
- ❖ Protects against bearing wear

Meets the performances:

API CH-4 / SL; ACEA E7

Technical Data:

TARMOND	Test method	
API		CH-4/SL
SAE Grade		15W-40
Density at 15°C gr/cm ³	ASTM D 1298	0,882
Viscosity at 40°C cSt	ASTM D 445	105-110
Viscosity at 100°C cSt	ASTM D 445	15-15,5
Viscosity Index	ASTM D 2270	Min. 132
Flash point °C	ASTM D 92	Min. 225
Pour point °C	ASTM D 97	-30

Above values are the typical values of the products and may vary with each batch.