



TAREX CVT Fluid

AUTOMATIC TRANSMISSION FLUID

Product Description:

TAREX CVT Fluid Automatic Transmission Fluid is a blend of synthetic base oils and highly sophisticated additive package especially formulated for the use in **C**ontinuously **V**ariable **T**ransmission (CVT). It has the critical frictional and viscosity characteristics required by the specified transmissions to provide superior performance and long service life with improved low and high temperature and anti-wear protection, especially for start and stop driving. The high quality synthetic base oils of TAREX CVT Automatic Transmission Fluid and an additive combination adapted to an optimum torque transmission will provide a reliable performance in a wide range CVT equipped vehicles. Special additives reduce energy loss due to friction, remove heat from rubbing surfaces, thus preventing them from wear-out.

Applications:

Especially developed for Continuously Variable Transmissions (CVT) in passenger cars and light commercial vehicles. It has very good suitability for a reliable transmission of maximum torque in Push-Belt or Chain-CVTs.

Benefits:

- ❖ Extended friction durability and a high level of torque capacity, enhanced driving comfort and reliable transmission of maximum torque
- ❖ Excellent cold flow behavior, reliable lubrication at start-up even at low temperatures
- ❖ Enhanced oxidative stability, longer fluid life and extended service interval even in challenging conditions
- ❖ Excellent extreme pressure and anti-wear performance, better protection of the transmission

Meets the Performances:

BMW 83 22 0 429 154/EZL 799A; Toyota CVTF TC/FE; VW/AUDI TL 521 80 (G 052 180); MB 236.20; Ford CVT23; Nissan NS-2/N-CVT; Honda HCF2/HMMF; Hyundai/Kia CVT-1/SP III

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test method	
		CVT
Density at 15°C gr/cm³	ASTM D 1298	0.84-0.85
Viscosity at 40°C cSt	ASTM D 445	35-38
Viscosity at 100°C cSt	ASTM D 445	7.2-7.4
Viscosity Index	ASTM D 2270	Min. 170
Flash point °C	ASTM D 92	220
Pour point °C	ASTM D 97	-42

Above values are the typical values of the products and may vary with each batch.