



TAREX AGRO F426 UTTO

TRANSMISSION AND HYDRAULIC SYSTEM OIL for TRACTORS

Product Description:

TAREX AGRO F426 UTTO Transmission and Hydraulic System Oil is an extra high-performance, multipurpose Universal Tractor Transmission Oil (UTTO), engineered to meet or exceed transmission and hydraulic fluid requirements. It is formulated for service top-up and refill of transmissions, final drives, and hydraulic systems of agricultural and industrial tractors and other off-highway equipment, especially those with oil-immersed brake systems. TAREX AGRO F426 UTTO is designed with special frictional characteristics to prevent squawk and chatter in wet brake systems and to deliver consistent braking performance.

Applications:

TAREX AGRO F426 UTTO Transmission and Hydraulic System Oil is recommended for use in tractors from most OEMs, especially those equipped with wet brake systems.

Benefits:

- ❖ Improved low-temperature stability
- ❖ Helps reduce wet brake noise
- ❖ Suitable for most agricultural machinery requirements
- ❖ Helps keep systems clean and operating smoothly
- ❖ All-season performance with consistent hydraulic operation

Meets the Specifications:

JD J20C; D Volvo VCE 1273.03; WB 101; CASE; MAT 3505/3525/3526; Vickers I286S, M2950S, M2952S; FORD ESN M2C86B-C; Allison C4; MF M1145; CAT TO-2; White Q1826; Denison HF0/HF1/HF2; ZF TE-ML 03E/F, 05F, 06E/F/K, ZF TE-ML 17E/21F

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test Method	
SAE Grade		F426
Density at 15 °C, gr/cm ³	ASTM D 1298	0.86-0.87
Viscosity at 40 °C, cSt	ASTM D 445	55 - 65
Viscosity at 100 °C, cSt	ASTM D 445	9.3 - 9.9
CCS Viscosity at -30 °C, mPa.s	ASTM D 5293	Max. 7000
Viscosity Index	ASTM D 2270	142
Flash Point, °C	ASTM D 92	226
Pour Point, °C	ASTM D 97	-42

Above values are the typical values of the products and may vary with each batch