



TAREX ATF VI

AUTOMATIC TRANSMISSION FLUID

Product Description:

TAREX ATF VI Automatic Transmission Fluid is a premium formulation based on synthetic base oils and highly sophisticated additive packages that provide superior protection and performance in transmissions, including extended service life, improved low- and high-temperature stability, and wear protection under severe service conditions. TAREX ATF VI's high-performance formulation using hydrocracked base oils provides outstanding oxidation resistance and anti-shudder durability. It is specially formulated to meet the needs of a broad range of light- and heavy-duty automatic transmissions fitted with or without torque converter lock-up clutches.

Applications:

Particularly recommended for use in automatic gearboxes, transfer cases, and power steering systems of American vehicle manufacturers such as GM, Ford, and Chrysler; Asian manufacturers including Honda, Hyundai, Kia, Isuzu, Mitsubishi, Nissan, and Toyota; and European manufacturers including Mercedes-Benz, Opel, and Volvo. Also suitable for use in older automatic gearboxes, torque converters, power steering systems, and certain hydraulic systems where DEXRON III-H or DEXRON II-D fluids are required.

Benefits:

- ❖ Helps improve fuel economy in vehicles equipped with automatic transmissions by reducing friction
- ❖ Improves transmission response at low temperatures
- ❖ Provides smoother shifting and reduced shift lag
- ❖ Provides anti-shudder performance to help prevent vibration at the engine flywheel
- ❖ Protects compact and heavily loaded gear components
- ❖ Helps extend service life with improved shear stability at high temperatures and oxidation resistance
- ❖ Provides anti-wear, anti-corrosion, and anti-foam properties

Meets the Specifications:

GM DEXRON VI; Ford MERCON V; Chrysler ATF-Plus/ATF+3; Allison C-4; MB 236.9; VW G 055-025-A2; Volvo 97335/97342; ZF TE-ML 05L/TE-ML 21L/TE-ML 16N/TE-ML 16Q/TE-ML 20F; JASO 1-A-LV-15; Toyota ATF T-IV/WS; PSA AL4

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test Method	
		ATF VI
Density at 15 °C, gr/cm ³	ASTM D 1298	0.84 - 0.85
Viscosity at 40 °C, cSt	ASTM D 445	30 - 35
Viscosity at 100°C, cSt	ASTM D 445	5.9 - 6.2
Viscosity Index	ASTM D 2270	170
Flash Point, °C	ASTM D 92	210
Pour Point, °C	ASTM D 97	-45

Above values are the typical values of the products and may vary with each batch.