



## **TAREX Blu 5W-30 C3**

### **FULL SYNTHETIC MOTOR OIL – SN/GF-5**

#### **Product Description:**

TAREX Blu 5W-30 C3 Full Synthetic Motor Oil – SN/GF-5 is a full synthetic engine oil formulated with high-quality synthetic base oils. It delivers high levels of fuel economy combined with enhanced wear protection, even under the most demanding operating conditions. The unique combination of high-quality synthetic base oils and performance additive components enables high-performance engines to achieve maximum levels of efficiency, torque, and horsepower while extending engine durability by minimizing wear and keeping the engine virtually free of harmful deposits.

#### **Applications:**

TAREX Blu 5W-30 C3 Full Synthetic Motor Oil – SN/GF-5 is recommended for turbocharged and high-powered passenger cars, trucks, sport utility vehicles, and other mobile or stationary engines.

#### **Benefits:**

- ❖ Provides improved fuel economy
- ❖ Reduces friction to maximize horsepower
- ❖ Excellent protection against the formation of sludge and harmful deposits
- ❖ Superior lubrication flow and pumpability at high and low temperatures
- ❖ Lower pour point reduces start-up wear during cold weather and provides superb cold-start protection
- ❖ High resistance to oxidation keeps the oil fresher for longer
- ❖ Outstanding wear protection for vehicles of all ages, lowering maintenance costs by keeping the engine clean and improving performance

#### **Meets the Specifications:**

API SN; ACEA A3/B3/B4/C2/C3; ILSAC GF-5; MB 229.31/229.51/229.52; Dexos 2®; GM 6094M/4718M; VW 502.00/505.01/504.00/507.00; Ford WSS M2C946-A/M2C961-A1; BMW LL04; Porsche C30; JASO DL-1; Honda HTO-06; Chrysler 6395; PSA B71 2290/2297; FIAT 9.55535-CR1

**Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals**

#### **Technical Data:**

<b>TAREX</b>	<b>Test Method</b>	
API		SN/GF-5
SAE Grade		5W-30
Density at 15 °C, gr/cm <sup>3</sup>	ASTM D 1298	0.85 - 0.86
Viscosity at 40 °C, cSt	ASTM D 445	68 - 72
Viscosity at 100 °C, cSt	ASTM D 445	11.5 - 12.2
CCS Viscosity at -30°C, mPa.s	ASTM D 5293	Max. 6600
Viscosity Index	ASTM D 2270	156
Flash Point, °C	ASTM D 92	225
Pour Point, °C	ASTM D 97	-42
Total Base Number, mg KOH/g	ASTM D 2896	7.6 – 8.0
Sulphated Ash, %	ASTM D 874	0.80

Above values are the typical values of the products and may vary with each batch.