



## TAREX Blu 5W-30 SL

SYNTHETIC MOTOR OIL - SL/CF

### Product Description:

TAREX Blu 5W-30 SL Synthetic Motor Oil – SL/CF is a fuel-economy synthetic motor oil developed according to the latest technology. Specially selected synthetic base stocks are combined with a well-balanced choice of advanced additives. The low viscosity reduces frictional loss in the engine and provides outstanding protection against wear. It saves fuel and extends engine service life. TAREX Blu 5W-30 SL Synthetic Motor Oil – SL/CF synthetic motor oil is always ready to protect at critical stages of start-stop driving conditions. It provides outstanding thermal and oxidation stability in line with OEM manufacturer recommendations.

### Applications:

It is designed for petrol and diesel engines, including turbochargers and fuel injection systems. The new formulation continues to meet the recommendations of major automotive builders (OEMs) throughout Europe, America, Japan, and Asia, meeting relevant industry norms with fuel economy and long-life performance. TAREX Blu 5W-30 SL Synthetic Motor Oil – SL/CF provides reliable all-season protection.

### Benefits:

- ❖ Excellent overall lubrication under cold conditions
- ❖ Outstanding fuel economy
- ❖ Quick cold-weather starting
- ❖ Very efficient anti-deposit and anti-black sludge performance, which maintains a clean engine
- ❖ Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperatures
- ❖ Neutralization of acids
- ❖ Exceptional oil film stability through anti-wear protection under all loads
- ❖ Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness
- ❖ Excellent resistance to oil degradation

### Meet the Specifications:

API SL/CF; ACEA A3/B4; VW 502.00/505.00 MB 229.1

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

### Technical Data:

TAREX	Test Method	
API		SL/CF
SAE Grade		5W-30
Density at 15 °C, gr/cm <sup>3</sup>	ASTM D 1298	0.85 - 0.86
Viscosity at 40 °C, cSt	ASTM D 445	66-74
Viscosity at 100 °C, cSt	ASTM D 445	11.5 - 12.2
Viscosity Index	ASTM D 2270	156
Flash Point, °C	ASTM D 92	225
Pour Point, °C	ASTM D 97	-41
Total Base Number, mg KOH/g	ASTM D 2896	7.5 – 8.0
Sulphated Ash, %	ASTM D 874	1.1

Above values are the typical values of the products and may vary with each batch