



TAREX Blu 5W-30 SN

FULL SYNTHETIC MOTOR OIL – SN/CF

Product Description:

TAREX Blu 5W-30 SN Full Synthetic Motor Oil – SN/CF is formulated with high-quality synthetic base oils. It has an advanced formulation with highly effective additives and is blended using the latest technology. It is a full synthetic engine oil specially designed with improved fuel efficiency. It offers superb cold-start protection and therefore significantly reduces engine wear. Special additives contribute to a significant reduction in engine noise. It provides outstanding oxidation stability, long service life properties, and extended drain intervals. It is produced to maintain the efficiency of vehicle emission reduction systems in both diesel and gasoline-powered automobiles.

Applications:

It is designed for petrol and diesel engines, including turbocharged and fuel-injected engines. The new formulation continues to meet the recommendations of major automotive builders (OEMs) throughout Europe, America, Japan, and Asia. TAREX Blu 5W-30 SN Full Synthetic Motor Oil – SN/CF provides reliable all-season protection.

Benefits:

- ❖ Excellent high-temperature/high shear performance
- ❖ Excellent overall lubrication at cold ambient temperatures
- ❖ Good fuel economy
- ❖ Maintains high oil pressure
- ❖ Very efficient anti-deposit and anti-black sludge performance, which maintains a clean engine
- ❖ Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperatures
- ❖ Neutralization of acids
- ❖ Exceptional oil film stability through anti-wear protection under all loads
- ❖ Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness

Meets the Specifications:

API SN/CF; ACEA A5/B5; BMW LL01; Renault RN 0700/0710; MB 229.3; VW 502.00/505.00; Ford WSS M2C9346-A/M2C929-A

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX	Test Method	
API		SN/CF
SAE Grade		5W-30
Density at 15 °C, gr/cm ³	ASTM D 1298	0.85 - 0.86
Viscosity at 40 °C, cSt	ASTM D 445	69 - 74
Viscosity at 100 °C, cSt	ASTM D 445	11.5 - 12.2
CCS Viscosity at -30 °C, mPa.s	ASTM D 5293	Max. 6600
Viscosity Index	ASTM D 2270	156
Flash Point, °C	ASTM D 92	225
Pour Point, °C	ASTM D 97	-42
Total Base Number, mg KOH/g	ASTM D 2896	7.5 – 8.0
Sulphated Ash, %	ASTM D 874	1.1

Above values are the typical values of the products and may vary with each batch.