



TAREX Blu 5W-40 C3

FULL SYNTHETIC MOTOR OIL – SN/GF-5

Product Description:

TAREX Blu 5W-40 C3 Full Synthetic Motor Oil – SN/GF-5 is a full synthetic engine oil formulated with high-quality synthetic base oils. It has an advanced formulation with highly effective additives. It is blended using the latest technology for the most demanding modern high-performance engines. It helps to extend engine life, combined with enhanced wear protection even under the most demanding operating conditions. The unique combination of high-quality synthetic base oils and performance additive components enables high-performance engines to achieve maximum levels of efficiency, torque, and horsepower while extending engine durability by minimizing wear and keeping the engine virtually free of harmful deposits. This is achieved through its Low SAPS (low content of sulphated ash, phosphorus, and sulphur) technology, which is compatible with diesel particulate filters (DPF).

Applications:

TAREX Blu 5W-40 C3 Full Synthetic Motor Oil – SN/GF-5 is suitable for all gasoline, gas, and diesel engines of passenger cars, light-duty commercial vehicles, and off-road SUVs requiring API SN/GF-5 with 5W-40 viscosity grade or as recommended by OEMs.

Benefits:

- ❖ Reduces friction to maximize horsepower
- ❖ Excellent protection against the formation of sludge and harmful deposits
- ❖ Superior lubrication flow and pumpability at high and low temperatures
- ❖ Lower pour point reduces start-up wear during cold weather and provides superb cold-start protection
- ❖ High resistance to oxidation keeps the oil fresher for longer
- ❖ Outstanding wear protection for vehicles of all ages, lowering maintenance costs by keeping the engine clean and improving performance

Meets the Specifications:

API SN; ACEA A3/B3/B4/C3; ILSAC GF-5; MB 229.31/229.51/229.52; Dexos 2®; GM 6094M/4718M; VW 502.00/505.01/504.00; Ford WSS M2C946-A/M2C929-A; BMW LL04; Porsche C30; JASO DL-1; Honda HTO-06; Chrysler 6395

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals

Technical Data:

TAREX	Test Method	
API		SN/GF-5
SAE Grade		5W-40
Density at 15 °C, gr/cm ³	ASTM D 1298	0.85 - 0.86
Viscosity at 40 °C, cSt	ASTM D 445	87 - 92
Viscosity at 100 °C, cSt	ASTM D 445	13.9 - 14.3
CCS Viscosity at -30 °C, mPa.s	ASTM D 5293	Max. 6600
Viscosity Index	ASTM D 2270	160
Flash Point, °C	ASTM D 92	235
Pour Point, °C	ASTM D 97	-42
Total Base Number, mg KOH/g	ASTM D 2896	7.6 – 8.0
Sulphated Ash, %	ASTM D 874	0,80

Above values are the typical values of the products and may vary with each batch.