



## **TAREX Red 10W-40 SL**

**SEMI-SYNTHETIC MOTOR OIL – SL/CF**

### **Product Description:**

TAREX Red 10W-40 is a high-performance motor oil developed according to the latest technology. Based on specially selected base stocks and state-of-the-art additive technology, it provides outstanding thermal and oxidation stability. It helps prevent the formation of sludge and deposits, contributing to prolonged engine life and supporting extended oil drain intervals, as permitted by the relevant engine manufacturer's recommendations. Excellent low-temperature fluidity facilitates cold starting and provides effective wear protection at low temperatures.

### **Applications:**

TAREX Red 10W-40 has been specially developed for gasoline, diesel, and LPG-fueled engines in passenger cars and light commercial vehicles. It is recommended for modern vehicles, including high-performance, turbocharged, multivalve, and direct-injection gasoline, diesel, and LPG engines. It meets the requirements of most European, North American, and Japanese vehicle manufacturers where API SL/CF performance level is specified.

### **Benefits:**

Excellent high- and low-temperature stability  
Promotes smoother operation, reduces friction, and supports fuel economy  
Detergent additives help maintain high engine cleanliness  
Advanced anti-wear technology helps extend engine life  
Helps minimize oil consumption

### **Meet the Specifications:**

API SL/CF; ACEA A3/B3/B4; VW 502/505; MB 229.1

**Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.**

### **Technical Data:**

<b>TAREX</b>	<b>Test Method</b>	
API		SL/CF
SAE Grade		10W-40
Density at 15 °C, gr/cm <sup>3</sup>	ASTM D 1298	0.87 - 0.88
Viscosity at 40 °C, cSt	ASTM D 445	98 - 106
Viscosity at 100 °C, cSt	ASTM D 445	13.9 - 14.7
Viscosity Index	ASTM D 2270	Min. 140
Sulfated Ash, Mass %	ASTM D 874	Max. 1.2
Total Base Number, mg KOH/g	ASTM D 2896	7.2
Flash Point, °C	ASTM D 92	225
Pour Point, °C	ASTM D 97	-35

Above values are the typical values of the products and may vary with each batch.