



TAREX TURBO 20W-50

MINERAL MOTOR OIL – CF-4

Product Description:

TAREX TURBO 20W-50 CF-4 is a high-quality fleet engine oil recommended for use in a wide range of American, European, and Japanese engines, for both on- and off-road equipment. It is designed to provide superior soot dispersancy and exceptional engine cleanliness through a balanced combination of selected additives and base oils. Its specialized formulation helps maintain engine cleanliness and provides effective protection in frequently used and high-mileage diesel engines. TAREX TURBO 20W-50 CF-4 meets the lubrication requirements where API CF-4 performance level is specified.

Applications:

Mixed fleets of diesel and gasoline engines; diesel engines in fishing boats, river boats, and ferries; agricultural tractors; off-highway diesel earthmoving machinery; and on-highway light- and heavy-duty diesel trucks and buses. Suitable for older, high-mileage engines.

Benefits:

- ❖ Provides effective lubrication and reliable protection for trucks, buses, and light trucks under moderate load operating conditions
- ❖ Effectively protects engine parts against wear, rust, and corrosion
- ❖ Good resistance to oxidation and aging, helping maintain stable viscosity properties

Meets the Specifications:

API CF-4; ACEA E2/B3; MB 228.1; Volvo VDS-2

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

| TAREX | Test Method | |
|--------------------------------------|--------------------|-------------|
| API | | CF-4 |
| SAE Grade | | 20W-50 |
| Density at 15 °C, gr/cm ³ | ASTM D 1298 | 0.89 |
| Viscosity at 40 °C, cSt | ASTM D 445 | 160 - 175 |
| Viscosity at 100 °C, cSt | ASTM D 445 | 18.5 - 19.5 |
| Viscosity Index | ASTM D 2270 | Min. 123 |
| Flash Point, °C | ASTM D 92 | 230 |
| Pour Point, °C | ASTM D 97 | -32 |

Above values are the typical values of the products and may vary with each batch.