



## TAREX TURBO 15W-40

DIESEL MOTOR OIL - CH-4/SL

### Product Description:

TAREX TURBO 15W-40 CH-4 is a heavy-duty multigrade diesel engine oil designed for use in high-speed, four-stroke diesel engines meeting the requirements of American, European, and Japanese engine manufacturers.

### Applications:

It is formulated for heavy-duty service in engines designed for on-highway operation, while also being suitable for a wide range of off-highway heavy-duty applications.

### Benefits:

- ❖ Helps control oil thickening and provides outstanding filterability
- ❖ Provides increased resistance to thermal breakdown
- ❖ Provides optimum protection against corrosion, piston deposits, oxidation, and sludge build-up
- ❖ High-level detergent-dispersant properties help keep the engine clean
- ❖ Protects against bearing wear

### Meets the Specifications:

API CH-4 / SL; ACEA E7

### Technical Data:

TARMOND	Test Method	
API		CH-4/SL
SAE Grade		15W-40
Density at 15 °C, gr/cm <sup>3</sup>	ASTM D 1298	0,882
Viscosity at 40 °C, cSt	ASTM D 445	105 - 110
Viscosity at 100 °C, cSt	ASTM D 445	15.0 – 15.5
Viscosity Index	ASTM D 2270	Min. 132
Flash Point, °C	ASTM D 92	Min. 225
Pour Point, °C	ASTM D 97	-30

Above values are the typical values of the products and may vary with each batch.