



## **TAREX TURBO UHPD 10W-40**

### **SYNTHETIC MOTOR OIL - CJ-4/SN**

#### **Product Description:**

TAREX TURBO UHPD 10W-40 Synthetic Motor Oil CJ-4/SN is a low-ash advanced synthetic heavy-duty diesel engine oil designed to help extend engine life under severe operating conditions. It is formulated using synthetic technology and high-quality base oils to deliver excellent performance in both new and older engines. The product meets the long-life requirements of major engine manufacturers and provides reliable protection over extended operating periods. TAREX TURBO UHPD 10W-40 Synthetic Motor Oil CJ-4/SN delivers effective lubrication for modern, high-performance, low-emission engines operating in severe applications.

#### **Applications:**

Suitable for heavy-duty fleets operating under severe conditions. Recommended for extended oil drain intervals in heavy-duty trucks, buses, and off-road machinery where API CJ-4/SN performance level is specified, including engines equipped with diesel particulate filters (DPF).

#### **Benefits:**

- ❖ Outstanding protection against oil thickening, high-temperature deposits, sludge build-up, and oil degradation
- ❖ Excellent anti-wear and anti-scuff properties, helping protect against bore polishing and corrosion
- ❖ Helps improve oil circulation
- ❖ Stay-in-grade shear stability with low volatility
- ❖ Helps maintain engine efficiency, support long engine life, and extend oil service life
- ❖ Helps improve corrosion protection and supports extended oil drain intervals

#### **Meets the Specifications:**

API CJ-4/SN; ACEA E6/E9/E7; MB 228.31/228.51; MAN M3477/3271/3677; Volvo VDS-4/VDS-3/CNG; Renault Truck RXD/RLD/RLD-2/RLD-3; Mack EO-M Plus/EO-N/EO-O; JASO DH-2, CAT ECF-3; Cummins CES 20081; Scania LDF-3

**Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.**

#### **Technical Data:**

<b>TAREX</b>	<b>Test Method</b>	
API		CJ-4/SN
SAE Grade		10W-40
Density at 15 °C, gr/cm <sup>3</sup>	ASTM D 1298	0.86 - 0.87
Viscosity at 40 °C, cSt	ASTM D 445	95 - 100
Viscosity at 100 °C, cSt	ASTM D 445	14.3 - 14.7
CCS Viscosity at -25 °C, mPa.s	ASTM D 5293	Max. 7000
Viscosity Index	ASTM D 2270	156
Flash Point, °C	ASTM D 92	Min. 220
Pour Point, °C	ASTM D 97	-41
Total Base Number, mg KOH/g	ASTM D 2896	9.5 - 10
Sulphated Ash, %	ASTM D 874	0.88

Above values are the typical values of the products and may vary with each batch