



## **TAREX AGRO 10W-40 CI-4**

### **ULTRA HIGH PERFORMANCE DIESEL TRACTOR OIL**

#### **Product Description:**

TAREX AGRO 10W-40 CI-4 Ultra High Performance Diesel Tractor Oil is an engine oil for use in heavy-duty turbo-diesel engines of tractors as well as in on- and off-highway equipment. The oil is engineered with synthetic-blend technology to meet the long-life requirements of major engine manufacturers and provides protection over extended service intervals. TAREX AGRO 10W-40 CI-4 Ultra High Performance Diesel Tractor Oil provides lubrication for modern, high-performance, low-emission engines used in severe applications. This engine oil is formulated with high-performance base oils that provide excellent low-temperature fluidity, high-temperature viscosity retention, and volatility control.

#### **Applications:**

Designed for use in the latest European, U.S., and Japanese tractors and heavy-duty on- and off-highway equipment, including the new generation of highly turbocharged, emission-controlled engines. It is a suitable choice for modern tractors and agricultural equipment.

#### **Benefits:**

- ❖ Outstanding protection against oil thickening, high-temperature deposits, sludge build-up, and oil degradation
- ❖ Excellent anti-wear and anti-scuff properties, with protection against bore polishing and corrosion
- ❖ Stay-in-grade shear stability with low volatility
- ❖ Good low-temperature properties

#### **Meets the Specifications:**

ACEA E7/E5; API CI-4, CH-4; Massey Ferguson 1139/1144; Ford New Holland M2C-159B; John Deere J27

**Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.**

#### **Technical Data:**

<b>TAREX</b>	<b>Test Method</b>	
API		CI-4
SAE Grade		10W-40
Density at 15 °C, gr/cm <sup>3</sup>	ASTM D 1298	0.86 - 0.87
Viscosity at 40 °C, cSt	ASTM D 445	95 - 100
Viscosity at 100 °C, cSt	ASTM D 445	14.4 - 14.9
CCS Viscosity at -35 °C, mPa.s	ASTM D 5293	Max. 7000
Viscosity Index	ASTM D 2270	155
Flash Point, °C	ASTM D 92	235
Pour Point, °C	ASTM D 97	-41
Total Base Number, mg KOH/g	ASTM D 2896	10.0 - 10.7
Sulphated Ash, %	ASTM D 874	1.3

Above values are the typical values of the products and may vary with each batch.