



## **TAREX BLU 5W-20 C3**

---

### **FULL SYNTHETIC MOTOR OIL**

#### **Product Description:**

TAREX Blu 5W-20 C3 Full Synthetic motor oil is a state of the art, advanced technology motor oil providing the highest level of engine protection available, even under the most severe operating conditions. Formulated with a special package of low sulphated ash, Phosphorus and Sulphur to resist filter plugging for diesel particulate filters. It provides exceptional resistance to high temperature oxidation thickening and prevents sludge formation commonly caused by moisture and combustion by-products. The exceptionally high viscosity index minimizes cold weather oil thickening, reducing battery drain and engine wear even at subzero startup temperatures.

#### **Applications:**

It is designed for petrol and diesel engines with particulate filters, incl. turbo charger and fuel injection. The new formulation continues to meet the latest technology of all major automotive builders (OEM) throughout Europe, America, Japan and Asia. With Tarex Blu 5W20 C3 Full Synthetic motor oil, you get the best in all-year protection.

#### **Benefits:**

- Excellent overall lubrication at extreme cold conditions
- Outstanding fuel economy versus mineral oils
- Quick cold weather starting
- Very efficient anti-deposit and anti-black sludge power which maintains a clean engine
- Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperature
- Neutralization of the acids
- Exceptional oil film stability through anti-wear protection in all loads
- Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness
- Fast oil flow for quicker engine warm-up at low temperature
- Reduces contact across engine parts

**Meet the performance:** API SN/CF, ACEA C5/C6, ILSAC GF5, Ford WSS-M2C945-A, FORD WSS-M2C960-A1, Ford WSS-M2C948-B, GM dexos1, VW 502/505.01, MB. 229.51/229.52, BMW LL04.

**Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.**



**Technical Data:**

TARMOND	Test method	
API		SN
SAE Grade		5W-20
Density at 15°C gr/cm <sup>3</sup>	ASTM D 1298	0.84 – 0.85
Viscosity at 40°C cSt	ASTM D 445	47 - 52
Viscosity at 100°C cSt	ASTM D 445	8.7 – 9.2
Viscosity Index	ASTM D 2270	160
Total Base Number mgKOH/g	ASTM D 2896	7.4
Sulfated Ash, mass %	ASTM D 874	0.8
Flash point °C	ASTM D 92	215
Pour point °C	ASTM D 97	-45

Above values are the typical values of the products and may vary with each batch.