



TAREX BLU 5W-30 C3

SYNTHETIC MOTOR OIL

Product Description:

TAREX BLU 5W-30 C3 is a new generation, fuel economy motor oil developed using the latest developments in synthetic technology, based on specially selected synthetic base-stocks, it is particularly well suited to modern multi-valve engines equipped with turbochargers and direct injection. Formulated with a special package of low sulphated ash, Phosphorus and Sulphur to resist filter plugging for diesel particulate filters. Additive technology ensures minimizing environmental damage. It reduces friction for maximum engine performance. TAREX BLU 5W-30 C3 brings high lubricating properties for better controlled oil consumption. It provides exceptional performance and protection for high-performance vehicles, while maintaining the efficiency of Car Emission Reduction Systems in both diesel and gasoline engines. It's special formulation resists the most extreme variations in operating temperature.

Applications:

It is designed for petrol and diesel engines, including turbo charger and fuel injection. The new formulation continues to meet the recommendation of all major automotive builders (OEM) throughout Europe, America, Japan and Asia norms with fuel economy, low ash and long-life performance. With the TAREX BLU 5W-30 C3 Synthetic motor oil you get the best in all-year protection.

Benefits:

- Excellent high-temperature/high shear performance
- Excellent overall lubrication at extreme cold conditions
- Outstanding fuel economy based on comparison versus those grades most commonly used mineral oils
- Quick cold weather starting
- Very efficient anti-deposit and anti-black sludge power which maintains a clean engine
- Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperature
- Neutralization of the acids
- Exceptional oil film stability through anti-wear protection in all loads
- Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness
- Smooth engine running
- Better controlled oil consumption
- Compatible with catalysts

Meet the performance: API SN/CF, ACEA C2/C3, A3/B3/B4, ILSAC GF-5, VW502/504/507, BMW LL-04, MB229.31/229.51/229.52, GM dexos2, Ford WSS-M2C917-A, PSA B712290

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.



Technical Data:

TAREX BLU 5W-30	Test method	
API		SN/CF
SAE Grade		5W-30
Density at 15°C, gr/cm ³	ASTM D 1298	0.86 – 0.87
Viscosity at 40°C, cSt	ASTM D 445	71 - 76
Viscosity at 100°C, cSt	ASTM D 445	11.5 – 12.2
Viscosity Index	ASTM D 2270	154
Flash point, °C	ASTM D 92	220
Pour point, °C	ASTM D 97	-42
Sulfated Ash, mass %	ASTM D 874	0.8
Total Base Number mgKOH/g	ASTM D 2896	7.4

Above values are the typical values of the products and may vary with each batch.