



TAREX BLU 5W-30 SN

SYNTHETIC MOTOR OIL

Product Description:

TAREX BLU 5W-30 SN motor oil specially formulated for helping your engine to operate at its full potential. The latest additive technology provides maximum engine protection even under the toughest driving conditions. It helps to prevent dirt and sludge build-up. It provides exceptional performance for modern high-performance vehicles. It is produced expertly to maintain the efficiency of Car Emission Reduction Systems in both diesel and gasoline powered engines. TAREX BLU 5W-30 SN Synthetic motor oil provides high lubricating properties such as wear protection and high temperature resistance for better controlled oil consumption.

Applications:

TAREX BLU 5W-30 SN motor oil is recommended for petrol, diesel engines, turbo-charged, fuel injection and high-powered passenger car, truck, sport utility vehicles as well as other mobile or stationary engines. The new formulation continues to meet the recommendation of all major automotive builders (OEM) throughout Europe, America, Japan and Asia norms with fuel economy, low ash and long-life performance.

Benefits:

- Excellent high-temperature/high shear performance
- Excellent overall lubrication at extreme cold conditions
- Outstanding fuel economy versus mineral oils
- Quick cold weather starting
- Very efficient anti-deposit and anti-black sludge power which maintains a clean engine
- Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperature
- Neutralization of the acids
- Exceptional oil film stability through anti-wear protection in all loads
- Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness
- Smooth engine running
- Optimum oil pressure under all operating conditions

Meets the performance: API SN/CF, ACEA A5/B5, VW 502/505, MB 229.5

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.



Technical Data:

TAREX BLU 5W-30	Test method	
API		SN/CF
SAE Grade		5W-30
Density at 15°C, gr/cm ³	ASTM D 1298	0.86 – 0.87
Viscosity at 40°C, cSt	ASTM D 445	71 – 75
Viscosity at 100°C, cSt	ASTM D 445	11.5 – 12.1
Viscosity Index	ASTM D 2270	152
Flash point, °C	ASTM D 92	220
Pour point, °C	ASTM D 97	-42
Sulfated Ash, mass %	ASTM D 874	1
Total Base Number mgKOH/g	ASTM D 2896	7.5 - 8

Above values are the typical values of the products and may vary with each batch.