



TAREX BLU 5W-40 SN

SYNTHETIC MOTOR OIL

Product Description:

TAREX Blu 5W-40 SN is a high performance engine oil based on selected synthetic base oils in combination with high performance additives. Designed with improved fuel efficiency performance. The special additives added contribute to a significant reduction in engine noise. It provides outstanding oxidation stability, long-life properties and extended drain intervals. TAREX Blu 5W-40 SN reduces oil and fuel consumption and that ensures fast lubrication of the engine. It is produced expertly to maintain the efficiency of Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Applications:

It is designed for petrol and diesel engines, including turbocharged and fuel injection. The new formulation continues to meet the recommendation of all major automotive builders (OEM) throughout Europe, America, Japan and Asia. With the TAREX Blu 5W-40 SN you get the best in all-year protection.

Benefits:

- Excellent high-temperature/high shear performance
- Excellent overall lubrication at cold ambient temperatures
- Good fuel economy
- Maintains high oil pressure
- Very efficient anti-deposit and anti-black sludge power which maintains a clean engine
- Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperature
- Neutralization of the acids
- Exceptional oil film stability through anti-wear protection in all loads
- Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness

Meets the performance: API SN/CF, ACEA A5/B5, VW 502/505, MB 229.5, BMW LL-01, Ford M2C-945A/946A/947A, Chrysler MS6395, GM 6094M, GM Dexos1, ILSAC GF-5

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.



Technical Data:

TARMOND	Test method	
API	-	SN/CF
SAE Grade	-	5W-40
Density at 15°C gr/cm ³	ASTM D 1298	0.865 – 0.875
Viscosity at 40°C cSt	ASTM D 445	88- 93
Viscosity at 100°C cSt	ASTM D 445	13.5 – 14.2
Viscosity Index	ASTM D 2270	150
Total Base Number mgKOH/g	ASTM D 2896	7.5
Flash point °C	ASTM D 92	230
Sulfated Ash, mass %	ASTM D 874	1.2 max.
Pour point °C	ASTM D 97	-42

Above values are the typical values of the products and may vary with each batch.