



## **TAREX BLU 5W-40**

---

### **SYNTHETIC MOTOR OIL**

#### **Product Description:**

TAREX Blu5W-40 is a high performance engine oil based on selected synthetic base oils in combination with high performance additives. Designed to meet the high performance standards for car manufacturers. It provides outstanding thermal and oxidation stability. It has active cleansing technology, prevents dirt build-up in engine parts. It can be used at constant high speed and "start-stop" duty on or off road under the most severe conditions. TAREX Blu 5W-40 helps provide long engine life. The special formulated additive package gives an outstanding protection at high temperature and pressure, typical for diesel engines of passenger cars, minivans and off-road vehicles.

#### **Applications:**

TAREX Blu5W-40 is recommended for all modern vehicles, including highperformance, turbo-charged, multi valve, direct injected gasoline, diesel and LPG fuelled engines of passenger cars and light commercial vehicles (in particular those equipped with pump injectors), minivans and off-road vehicles.

#### **Benefits:**

- Excellent high temperatures/high shear performance
- Maintains high oil pressure
- Very efficient anti-deposit and anti-black sludge power which maintains a clean engine
- Prevention of carbon and lacquer deposits on vital moving parts caused by very high engine temperature
- Neutralization of the acids
- Exceptional oil film stability through anti-wear protection in all loads
- Outstanding thermal stability and oil oxidation resistance to maintain a high standard of piston cleanliness
- Low viscosity improves fuel efficiency
- Smooth engine operation

**Meet the performance:** API SL/CF, ACEA A3/B3-B4, VW 502/505, MB 229.3

**Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.**



**Technical Data:**

TARMOND	Test method	
API	-	SL/CF
SAE Grade	-	5W-40
Density at 15°C gr/cm <sup>3</sup>	ASTM D 1298	0.87 – 0.88
Viscosity at 40°C cSt	ASTM D 445	90-97
Viscosity at 100°C cSt	ASTM D 445	13.5-14.2
Viscosity Index	ASTM D 2270	150
Total Base Number mgKOH/g	ASTM D 2896	7
Flash point °C	ASTM D 92	225
Sulfated Ash, mass %	ASTM D 874	1.2 max.
Pour point °C	ASTM D 97	-37

Above values are the typical values of the products and may vary with each batch.