



TAREX RED 10W-30

SEMI-SYNTHETIC MOTOR OIL

Product Description:

TAREX RED 10W-30 is fuel economy and high performance semi-synthetic motor oil developed according the most recent technology. Based on specially selected base-stocks and high performance additive technology, it provides outstanding thermal and oxidation stability preventing premature degradation at high temperatures. Sludge can block your engine's oil pathways and damage your engine's performance, TAREX RED 10W-30 protects engine against sludge formation. It provides extended oil drain intervals as permitted by the relevant engine manufacturer's recommendations. It has high shear stability to allow lubricant to stay-on-grade viscosity.

Applications:

TAREX RED 10W-30 is recommended for use in most modern cars, vans and light trucks including multi valve techniques and those vehicles fitted with or without catalytic convertors, operating under most severe driving conditions. It is also recommended for use in unleaded, LPG and turbo vehicles, as well as normally aspirated and turbo charged light diesel engines.

Benefits:

- Smoother, reduces friction, improved fuel economy and filterability
- Excellent fluidity at low temperature ensures good starting and longer maintenance intervals
- Excellent high and low temperature stability
- Cleaner, detergency additives perform very high engine cleanliness
- Exceptional anti-wear molecule technology for longer engine life
- Reduced oil consumption between oil changes
- Reduced lower emissions
- Outstanding lubrication characteristics in all seasons
- Excellent protection against oxidation and foaming
- Protection against thermal break down

Meet the performance: API SL/CF, ACEA A3/B3-B4, VW 502/505, MB 229.1

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.



Technical Data:

TAREX 10W-30	Test method	
API		SL - CF
SAE Grade		10W - 30
Density at 15°C gr/cm ³	ASTM D 1298	0.87 – 0.88
Viscosity at 40°C cSt	ASTM D 445	80 - 85
Viscosity at 100°C cSt	ASTM D 445	11.7 - 12.5
Viscosity Index min.	ASTM D 2270	140
Sulfated Ash, mass %	ASTM D 874	1.2
Total Base Number mgKOH/g	ASTM D 2896	7.2
Flash point °C	ASTM D 92	220
Pour point °C	ASTM D 97	-35

Above values are the typical values of the products and may vary with each batch.