



TAREX RED 10W-40

SEMI-SYNTHETIC MOTOR OIL

Product Description:

TAREX RED 10W-40 is semi-synthetic motor oil developed according to the most recent additive technology in combination with specially selected synthetic base-stocks. Advanced formulation helps to protect the engine against wear and provides long-lasting engine performance. High viscosity index allows the engine oil to operate efficiently over a wide temperature range. It helps prevent dirt build-up throughout the engine parts. TAREX RED 10W-40 provides outstanding thermal and oxidation stability, extended oil drain intervals as permitted by the engine manufacturer (OEM).

Applications:

TAREX 10W-40 is suitable for use in direct fuel injected, turbocharged as well as older type of diesel engines. It is a high quality lubricant for passenger cars and light trucks.

Benefits:

- Excellent high and low temperature stability
- Cleaner, detergent additives perform very high engine cleanliness
- Exceptional anti-wear molecule technology for longer engine life
- Provides high lubrication
- Reduced oil consumption and lower emission
- Provides excellent protection for all driving conditions

Meet the performance: API SN/CF, ACEA A3/B3-B4, VW 502/505, MB. 229.3

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.



Technical Data:

| TARMOND | Test method | |
|------------------------------------|-------------|-------------|
| API | | SN/CF |
| SAE Grade | | 10W-40 |
| Density at 15°C gr/cm ³ | ASTM D 1298 | 0.875 |
| Viscosity at 40°C cSt | ASTM D 445 | 95 - 105 |
| Viscosity at 100°C cSt | ASTM D 445 | 13.6 – 14.4 |
| Viscosity Index | ASTM D 2270 | 140 |
| Flash Point °C | ASTM D 92 | 225 |
| Total Base Number mg KOH/g | ASTM D 2896 | 7.4 |
| Pour Point °C | ASTM D 97 | -35 |

Above values are the typical values of the products and may vary with each batch.