

TAREX TURBO 15W-40 CF-4

SUPER HIGH PERFORMANCE DIESEL OIL

Product Description:

TAREX TURBO 15W-40 CF-4 is a high quality fleet engine oil recommended for use in a wide range of American, European and Japanese engines, both on and off-road equipments. It has been designed to provide superior soot dispersancy and exceptional cleanliness through the use of a unique combination of selected additives and base oils. Its special formula provides engine parts cleanliness and effective protection in frequently used and high mileage diesel engines. TAREX TURBO 15W-40 CF-4 completely fulfill the lubrication requirements.

Applications:

It is designed for use in naturally aspirated and turbocharged diesel engines working under severe conditions.

Benefits:

- Provides effective lubrication and reliable protection in trucks, buses and light trucks under moderate loaded operating conditions
- Protects effectively all engine parts against wear, rust and corrosion
- Stable to oxidation and aging, keeps stable viscosity properties

Meet the performance: API CF-4, ACEA E3-96, MB 228.1, Volvo VDS

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.

Technical Data:

TAREX TURBO 15W-40 CF-4	Test method	
API		CF-4
SAE Grade		15W-40
Density at 15°C gr/cm³	ASTM D 1298	0.878
Viscosity at 40°C cSt	ASTM D 445	105-110
Viscosity at 100°C cSt	ASTM D 445	14.5-15.6
Viscosity Index min.	ASTM D 2270	132
Flash point °C	ASTM D 92	225
Pour point °C	ASTM D 97	-33

Above values are the typical values of the products and may vary with each batch.