



TAREX TURBO 15W-40 CJ-4

UHPD LOW SAPS 15W-40 CJ-4

Product Description:

TAREX TURBO UHPD LOW SAPS 15W-40 CJ-4 is an Ultra High Performance Diesel (UHPD) engine oil for use in low saps turbo-diesel engines of trucks, buses and industrial engines. The oil is engineered with meet the long-life requirements of major engine manufacturers and gives protection over a long time period.

TAREX TURBO UHPD LOW SAPS 15W-40 CJ-4 provides lubrication to modern, high performance, low emissions engines used in severe applications. This engine oil is designed using the highly refined base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control.

Applications:

Suitable for heavy-duty fleets working under severe conditions. Suitable for extended oil drain intervals in heavy duty trucks, buses and off-road machinery where API CJ-4 performance level is recommended.

Benefits:

- Outstanding protection against oil thickening, high temperature deposits, sludge build-up and oil degradation
- Excellent anti-wear, anti-scuff properties with bore polishing and corrosion protection
- Stay-in-grade shear stability with low volatility
- Good low temperature properties
- Provides lower oil consumption by combating piston deposits
- Excellent engine power all the way through the oil drain
- Helps to maintain long engine life and long oil life
- Provides longer oil change intervals by fighting contaminants

Meets Performance: ACEA: E9/E6/E7, API: CJ-4/CI-4+, VOLVO: VDS-4/VDS-3, IVECO: T2 E7, JASO: DH-2, SCANIA: LDF-LA, RENAULT TRUCK RXD/RLD-3, MTU: CATEGORY 2, MB 228.51/228.31, MAN: M3677, MACK: EO-O PREMIUM PLUS, DEUTZ: DQC III-05, DDC: 93K218, CUMMINS: CES 20081/77/72/71, CAT: ECF-2/ECF-3

Please check your owner's manual for the manufacturer's recommended oil viscosity grade and API classification and approvals.



Technical Data:

TARMOND	Test method	
API		CJ-4
SAE Grade		15W-40
Density at 15°C gr/cm ³	ASTM D 1298	0.882
Viscosity at 40°C cSt	ASTM D 445	105-110
Viscosity at 100°C cSt	ASTM D 445	14-15
Viscosity Index	ASTM D 2270	136
Flash point °C	ASTM D 92	229
Pour point °C	ASTM D 97	-37
Total Base No (TBN)	ASTM 2896	9.4
Sulphated Ash %	ASTM D874	0.9 max

Above values are the typical values of the products and may vary with each batch.